



# EVERPURE® CB20-124E WATER FILTER HOUSING

## HIGH FLOW BIG BOWL HOUSING

CGS-23 10" Parallel Filter Housing: EV9100-31



### APPLICATIONS

Foodservice

### FEATURES • BENEFITS

High pressure housing includes head, mounting bracket and bowl

Integral outlet pressure gauge monitors operation

Complete modular package lets you expand capacity as needed

### INSTALLATION TIPS

Choose a mounting location which is suitable to support the full weight of the system when operating (30 lbs. [13.6 kg]).

3/4" FNPT inlet and outlet connection.

Install on cold water lines only.

Do not install where unit is exposed to direct sunlight.

Allow a minimum of 4" (10.16 cm) clearance under the filter to facilitate cartridge change.

Do not braze or solder fittings into head.

Never use a saddle valve for connection.

### OPERATION TIPS

Change cartridges on a regular six (6) month preventative maintenance program.

Change cartridges when the difference between the inlet pressure and the system outlet gauge is greater than or equal to 20 psi (1.4 bar).

Service flow rate must not exceed 5.0 gpm (19 Lpm).

Always flush the filter cartridge to drain for fifteen minutes at time of installation and cartridge change.

### SIZING

Service Flow Rate: Maximum 5 gpm (19 Lpm)