

**Model 6HK60/144**  
**Air-Cooled Portable Air Conditioner**  
**Submittal Data**



SD-6HK60/144-4

**STANDARD FEATURES**

- All Steel, Painted Cabinets
- Internal Thermostat Settings
- Internally Insulated with Fiberglass Insulation
- R410a Refrigerant
- Fork Lift Slots and Lifting Lugs Standard
- Heavy Duty 4 Wheel Casters
- Cleanable Filters



**SPECIFICATIONS**

Model	6HK60BGA2ACA0	6HK144BBA2ACA0	6HK144BEA2ACA0
Cooling Capacity	60,000 Btu/h	144,400 Btu/h	144,400 Btu/h
Power Supply - V/P/Hz	208/230-1-60	230-3-60	460-3-60
Dimensions	29.5" W x 62.1" D x 58.1" H	34.3" W x 75" D x 71" H	34.3" W x 75" D x 71" H
Supply Duct Dia	Evap 16"	14" (2)	
Connection	Condenser 20"	18"	
Return Duct Dia	Evap 16"	14" (2)	
Connection	Condenser N/A	18"	
Weight	661 lbs.	1168.4 lbs.	1168.4 lbs.
Amp Draw	32 A	54 A	27 A
Air Filter Material	Vinyl Chloride		
Refrigerant	R-410a		
Operating Temp	64 - 113°F		
Condensate	Drain		
Typical Cooling Area	1830 sq. ft	3,767 - 4,951 sq. ft	



**260 North Elm St.**  
 Westfield, MA 01085  
**Phone:** 413-564-5520  
**Fax:** 413-564-5815  
 www.Koldwave.com

Project: \_\_\_\_\_ Date: \_\_\_\_\_  
 Location: \_\_\_\_\_  
 Customer: \_\_\_\_\_  
 Engineer: \_\_\_\_\_  
 Submitted By: \_\_\_\_\_  
 For:  Reference  Approval  Construction  
 Unit Designation: \_\_\_\_\_  
 Schedule Number: \_\_\_\_\_